BRONZE LIFT

FACT SHEET

XP Series

Серия XP от Bronze Lift создана для тех, кто требует совершенства. Сочетая передовые технологии, превосходные характеристики и утонченную эстетику, лифты XP заново определяют понятие роскоши в вертикальном транспорте.

Грузоподъёмность и размеры кабины

Таблица прокручивается по горизонтали. Все размеры в миллиметрах, если не указано иное.

100

Номинальная грузоподъёмность	Пассажиров	Скорость	Макс. высота подъёма	Макс. остановок	Входы	Кабина Ширина	Кабина Глубина	Кабина Высота	Масса кабины	Дверь Ширина	Дверь Высота	Верхний габарит	Приямок	Мин. расстояние между этажами
450 kg	6	1	40	16	Один	1 000	1 250	2100 – 2700	900	800 – 1000	2000 – 2500	3 300	1 100	2 700
450 kg	6	1	40	16	Проходная	1 000	1 250	2100 – 2700	900	800 – 1000	2000 – 2500	3 300	1 100	2 700
450 kg	6	1,6	60	21	Один	1 000	1 250	2100 – 2700	900	800 – 1000	2000 – 2500	3 600	1 400	2 700
450 kg	6	1,6	60	21	Проходная	1 000	1 250	2100 – 2700	900	800 – 1000	2000 – 2500	3 600	1 400	2 700
630 kg	8	1	40	16	Один	1 100	1 400	2100 – 2700	1 200	800 – 1100	2000 – 2500	3 300	1 100	2 700
630 kg	8	1	40	16	Проходная	1 100	1 400	2100 – 2700	1 200	800 – 1100	2000 – 2500	3 300	1 100	2 700
630 kg	8	1,6	60	21	Один	1 100	1 400	2100 – 2700	1 200	800 – 1100	2000 – 2500	3 600	1 400	2 700
630 kg	8	1,6	60	21	Проходная	1 100	1 400	2100 – 2700	1 200	800 – 1100	2000 – 2500	3 600	1 400	2 700
800 kg	10	1	40	16	Один	1 350	1 400	2100 – 2700	1 500	800 – 1100	2000 – 2500	3 300	1 100	2 700
800 kg	10	1	40	16	Проходная	1 350	1 400	2100 – 2700	1 500	800 – 1100	2000 – 2500	3 300	1 100	2 700
800 kg	10	1,6	60	21	Один	1 350	1 400	2100 – 2700	1 500	800 – 1100	2000 – 2500	3 600	1 400	2 700
800 kg	10	1,6	60	21	Проходная	1 350	1 400	2100 – 2700	1 500	800 – 1100	2000 – 2500	3 600	1 400	2 700
1.000 kg (depth)	13	1	40	16	Один	1 100	2 100	2100 – 2700	1 800	800 – 1100	2000 – 2500	3 300	1 100	2 700
1.000 kg (depth)	13	1	40	16	Проходная	1 100	2 100	2100 – 2700	1 800	800 – 1100	2000 – 2500	3 300	1 100	2 700
1.000 kg (depth)	13	1,6	60	21	Один	1 100	2 100	2100 – 2700	1 800	800 – 1100	2000 – 2500	3 600	1 400	2 700
1.000 kg (depth)	13	1,6	60	21	Проходная	1 100	2 100	2100 – 2700	1 800	800 – 1100	2000 – 2500	3 600	1 400	2 700
1.000 kg (wide)	13	1	40	16	Один	1 600	1 400	2100 – 2700	1 800	800 – 1300	2000 – 2500	3 300	1 100	2 700
1.000 kg (wide)	13	1	40	16	Проходная	1 600	1 400	2100 – 2700	1 800	800 – 1300	2000 – 2500	3 300	1 100	2 700

Номинальная грузоподъёмность	Пассажиров	Скорость	Макс. высота подъёма	Макс. остановок	Входы	Кабина Ширина	Кабина Глубина	Кабина Высота	Масса кабины	Дверь Ширина	Дверь Высота	Верхний габарит	Приямок	Мин. расстояние между этажами
1.000 kg (wide)	13	1,6	60	21	Один	1 600	1 400	2100 – 2700	1 800	800 – 1300	2000 – 2500	3 600	1 400	2 700
1.000 kg (wide)	13	1,6	60	21	Проходная	1 600	1 400	2100 – 2700	1 800	800 – 1300	2000 – 2500	3 600	1 400	2 700

Номинальная грузоподъёмность	Пассажиров	Скорость	Макс. высота подъёма	Макс. остановок	Входы	Кабина Ширина	Кабина Глубина	Кабина Высота	Масса кабины	Дверь Ширина	Дверь Высота	Верхний габарит	Приямок	Мин. расстояние между этажами
630 kg	8	2	80	30	Один	1 100	1 400	2100 – 2700	1 200	800 – 1100	2000 – 2500	4 100	1 500	2 700
630 kg	8	2	80	30	Проходная	1 100	1 400	2100 – 2700	1 200	800 – 1100	2000 – 2500	4 100	1 500	2 700
630 kg	8	2,5	120	40	Один	1 100	1 400	2100 – 2700	1 200	800 – 1100	2000 – 2500	4 400	1 950	2 700
630 kg	8	2,5	120	40	Проходная	1 100	1 400	2100 – 2700	1 200	800 – 1100	2000 – 2500	4 400	1 950	2 700
800 kg	10	2	80	30	Один	1 350	1 400	2100 – 2700	1 500	800 – 1100	2000 – 2500	4 100	1 500	2 700
800 kg	10	2	80	30	Проходная	1 350	1 400	2100 – 2700	1 500	800 – 1100	2000 – 2500	4 100	1 500	2 700
800 kg	10	2,5	120	40	Один	1 350	1 400	2100 – 2700	1 500	800 – 1100	2000 – 2500	4 400	1 950	2 700
800 kg	10	2,5	120	40	Проходная	1 350	1 400	2100 – 2700	1 500	800 – 1100	2000 – 2500	4 400	1 950	2 700
1.000 kg (depth)	13	2	80	30	Один	1 100	2 100	2100 – 2700	1 800	800 – 1100	2000 – 2500	4 100	1 500	2 700
1.000 kg (depth)	13	2	80	30	Проходная	1 100	2 100	2100 – 2700	1 800	800 – 1100	2000 – 2500	4 100	1 500	2 700
1.000 kg (depth)	13	2,5	120	40	Один	1 100	2 100	2100 – 2700	1 800	800 – 1100	2000 – 2500	4 400	1 950	2 700
1.000 kg (depth)	13	2,5	120	40	Проходная	1 100	2 100	2100 – 2700	1 800	800 – 1100	2000 – 2500	4 400	1 950	2 700
1.000 kg (wide)	13	2	80	30	Один	1 600	1 400	2100 – 2700	1 800	800 – 1300	2000 – 2500	4 100	1 500	2 700
1.000 kg (wide)	13	2	80	30	Проходная	1 600	1 400	2100 – 2700	1 800	800 – 1300	2000 – 2500	4 100	1 500	2 700
1.000 kg (wide)	13	2,5	120	40	Один	1 600	1 400	2100 – 2700	1 800	800 – 1300	2000 – 2500	4 400	1 950	2 700
1.000 kg (wide)	13	2,5	120	40	Проходная	1 600	1 400	2100 – 2700	1 800	800 – 1300	2000 – 2500	4 400	1 950	2 700

Номинальная грузоподъёмность	Пассажиров	Скорость	Макс. высота подъёма	Макс. остановок	Входы	Кабина Ширина	Кабина Глубина	Кабина Высота	Масса кабины	Дверь Ширина	Дверь Высота	Верхний габарит	Приямок	Мин. расстояние между этажами
1.250kg	16	1	40	16	Один	1 200	2 300	2100 – 2700	2 000	900 – 1100	2000 – 2500	3 500	1 250	2 700
1.250kg	16	1	40	16	Проходная	1 200	2 300	2100 – 2700	2 000	900 – 1100	2000 – 2500	3 500	1 250	2 700
1.250kg	16	1,6	80	21	Один	1 200	2 300	2100 – 2700	2 000	900 – 1100	2000 – 2500	3 750	1 500	2 700
1.250kg	16	1,6	80	21	Проходная	1 200	2 300	2100 – 2700	2 000	900 – 1100	2000 – 2500	3 750	1 500	2 700
1.600kg	20	1	40	16	Один	1 400	2 400	2100 – 2700	2 200	900 – 1300	2000 – 2500	3 500	1 250	2 700
1.600kg	20	1	40	16	Проходная	1 400	2 400	2100 – 2700	2 200	900 – 1300	2000 – 2500	3 500	1 250	2 700
1.600kg	20	1,6	80	21	Один	1 400	2 400	2100 – 2700	2 200	900 – 1300	2000 – 2500	3 750	1 500	2 700
1.600kg	20	1,6	80	21	Проходная	1 400	2 400	2100 – 2700	2 200	900 – 1300	2000 – 2500	3 750	1 500	2 700
2.000kg	26	1	40	16	Один	1 500	2 700	2100 – 2700	2 600	1000 – 1400	2000 – 2500	3 750	1 350	2 700
2.000kg	26	1	40	16	Проходная	1 500	2 700	2100 – 2700	2 600	1000 – 1400	2000 – 2500	3 750	1 350	2 700
2.000kg	26	1,6	80	21	Один	1 500	2 700	2100 – 2700	2 600	1000 – 1400	2000 – 2500	4 000	1 600	2 700
2.000kg	26	1,6	80	21	Проходная	1 500	2 700	2100 – 2700	2 600	1000 – 1400	2000 – 2500	4 000	1 600	2 700
2.500kg	33	1	40	16	Один	1 800	2 700	2100 – 2700	3 000	1000 – 1400	2000 – 2500	3 750	1 350	2 700
2.500kg	33	1	40	16	Проходная	1 800	2 700	2100 – 2700	3 000	1000 – 1400	2000 – 2500	3 750	1 350	2 700
2.500kg	33	1,6	80	21	Один	1 800	2 700	2100 – 2700	3 000	1000 – 1400	2000 – 2500	4 000	1 600	2 700
2.500kg	33	1,6	80	21	Проходная	1 800	2 700	2100 – 2700	3 000	1000 – 1400	2000 – 2500	4 000	1 600	2 700

Номинальная грузоподъёмность	Пассажиров	Скорость	Макс. высота подъёма	Макс. остановок	Входы	Кабина Ширина	Кабина Глубина	Кабина Высота	Масса кабины	Дверь Ширина	Дверь Высота	Верхний габарит	Приямок	Мин. расстояние между этажами
1.250kg	16	2	80	30	Один	1 200	2 300	2100 – 2700	2 000	900 – 1100	2000 – 2500	4 250	1 600	2 700
1.250kg	16	2	80	30	Проходная	1 200	2 300	2100 – 2700	2 000	900 – 1100	2000 – 2500	4 250	1 600	2 700
1.250kg	16	2,5	120	40	Один	1 200	2 300	2100 – 2700	2 000	900 – 1100	2000 – 2500	4 500	2 050	2 700
1.250kg	16	2,5	120	40	Проходная	1 200	2 300	2100 – 2700	2 000	900 – 1100	2000 – 2500	4 500	2 050	2 700
1.600kg	20	2	80	30	Один	1 400	2 400	2100 – 2700	2 200	900 – 1300	2000 – 2500	4 250	1 600	2 700
1.600kg	20	2	80	30	Проходная	1 400	2 400	2100 – 2700	2 200	900 – 1300	2000 – 2500	4 250	1 600	2 700
1.600kg	20	2,5	120	40	Один	1 400	2 400	2100 – 2700	2 200	900 – 1300	2000 – 2500	4 500	2 050	2 700
1.600kg	20	2,5	120	40	Проходная	1 400	2 400	2100 – 2700	2 200	900 – 1300	2000 – 2500	4 500	2 050	2 700
2.000kg	26	2	80	30	Один	1 500	2 700	2100 – 2700	2 600	1000 – 1400	2000 – 2500	4 400	1 750	2 700
2.000kg	26	2	80	30	Проходная	1 500	2 700	2100 – 2700	2 600	1000 – 1400	2000 – 2500	4 400	1 750	2 700
2.000kg	26	2,5	120	40	Один	1 500	2 700	2100 – 2700	2 600	1000 – 1400	2000 – 2500	4 700	2 250	2 700
2.000kg	26	2,5	120	40	Проходная	1 500	2 700	2100 – 2700	2 600	1000 – 1400	2000 – 2500	4 700	2 250	2 700
2.500kg	33	2	80	30	Один	1 800	2 700	2100 – 2700	3 000	1000 – 1400	2000 – 2500	4 400	1 750	2 700
2.500kg	33	2	80	30	Проходная	1 800	2 700	2100 – 2700	3 000	1000 – 1400	2000 – 2500	4 400	1 750	2 700
2.500kg	33	2,5	120	40	Один	1 800	2 700	2100 – 2700	3 000	1000 – 1400	2000 – 2500	4 700	2 250	2 700
2.500kg	33	2,5	120	40	Проходная	1 800	2 700	2100 – 2700	3 000	1000 – 1400	2000 – 2500	4 700	2 250	2 700

Номинальная грузоподъёмность	Пассажиров	Скорость	Макс. высота подъёма	Макс. остановок	Входы	Кабина Ширина	Кабина Глубина	Кабина Высота	Масса кабины	Дверь Ширина	Дверь Высота	Верхний габарит	Приямок	Мин. расстояние между этажами
3.000kg	40	1	40	16	Один	2 000	2 800	2100 – 2700	3 500	1400 – 2000	2000 – 2500	3 900	1 600	2 700
3.000kg	40	1	40	16	Проходная	2 000	2 800	2100 – 2700	3 500	1400 – 2000	2000 – 2500	3 900	1 600	2 700
3.000kg	40	1,6	60	20	Один	2 000	2 800	2100 – 2700	3 500	1400 – 2000	2000 – 2500	4 200	1 800	2 700
3.000kg	40	1,6	60	20	Проходная	2 000	2 800	2100 – 2700	3 500	1400 – 2000	2000 – 2500	4 200	1 800	2 700
3.500kg	46	1	40	16	Один	2 100	3 050	2100 – 2700	3 500	1400 – 2000	2000 – 2500	3 900	1 600	2 700
3.500kg	46	1	40	16	Проходная	2 100	3 050	2100 – 2700	3 500	1400 – 2000	2000 – 2500	3 900	1 600	2 700
3.500kg	46	1,6	60	20	Один	2 100	3 050	2100 – 2700	3 500	1400 – 2000	2000 – 2500	4 200	1 800	2 700
3.500kg	46	1,6	60	20	Проходная	2 100	3 050	2100 – 2700	3 500	1400 – 2000	2000 – 2500	4 200	1 800	2 700
4.000kg	53	1	40	16	Один	2 400	2 900	2100 – 2700	3 500	1400 – 2000	2000 – 2500	3 900	1 600	2 700
4.000kg	53	1	40	16	Проходная	2 400	2 900	2100 – 2700	3 500	1400 – 2000	2000 – 2500	3 900	1 600	2 700
4.000kg	53	1,6	60	20	Один	2 400	2 900	2100 – 2700	3 500	1400 – 2000	2000 – 2500	4 200	1 800	2 700
4.000kg	53	1,6	60	20	Проходная	2 400	2 900	2100 – 2700	3 500	1400 – 2000	2000 – 2500	4 200	1 800	2 700
5.000kg	65	1	40	16	Один	3 000	3 250	2100 – 2700	3 500	1400 – 2000	2000 – 2500	4 200	1 800	2 700
5.000kg	65	1	40	16	Проходная	3 000	3 250	2100 – 2700	3 500	1400 – 2000	2000 – 2500	4 200	1 800	2 700

Размеры шахты

Номинальная грузоподъёмность	Скорость	Входы	Ширина · Боковое · 2P	Ширина · Центральное · 2P	Глубина, дверь внутри шахты · Боковое · 2P	Глубина, дверь в нише · Боковое · 2P	Глубина, дверь внутри шахты · Центральное · 2P	Глубина, дверь в нише · Центральное · 2P
450 kg	1	Один	1 520	1 750	1 650	1 595	1 590	1 550
450 kg	1	Проходная	1 520	1 750	1 890	1 780	1 770	1 730
450 kg	1,6	Один	1 520	1 750	1 650	1 595	1 590	1 550
450 kg	1,6	Проходная	1 520	1 750	1 890	1 780	1 770	1 730
630 kg	1	Один	1 620	1 970	1 800	1 750	1 740	1 700
630 kg	1	Проходная	1 620	1 970	2 040	1 940	1 920	1 880
630 kg	1,6	Один	1 620	1 970	1 800	1 750	1 740	1 700
630 kg	1,6	Проходная	1 620	1 970	2 040	1 940	1 920	1 880
800 kg	1	Один	1 850	2 100	1 800	1 750	1 740	1 700
800 kg	1	Проходная	1 850	2 100	2 040	1 940	1 920	1 880
800 kg	1,6	Один	1 850	2 100	1 800	1 750	1 740	1 700
800 kg	1,6	Проходная	1 850	2 100	2 040	1 940	1 920	1 880
1.000 kg (depth)	1	Один	1 620	1 970	2 500	2 445	2 450	2 410
1.000 kg (depth)	1	Проходная	1 620	1 970	2 740	2 630	2 640	2 600
1.000 kg (depth)	1,6	Один	1 620	1 970	2 500	2 445	2 450	2 410
1.000 kg (depth)	1,6	Проходная	1 620	1 970	2 740	2 630	2 640	2 600
1.000 kg (wide)	1	Один	2 120	2 150	1 800	1 750	1 740	1 700
1.000 kg (wide)	1	Проходная	2 120	2 150	2 040	1 940	1 920	1 880
1.000 kg (wide)	1,6	Один	2 120	2 150	1 800	1 750	1 740	1 700
1.000 kg (wide)	1,6	Проходная	2 120	2 150	2 040	1 940	1 920	1 880

Номинальная грузоподъёмность	Скорость	Входы	Ширина · Боковое · 2P	Ширина · Центральное · 2P	Глубина, дверь внутри шахты · Боковое · 2P	Глубина, дверь в нише · Боковое · 2P	Глубина, дверь внутри шахты · Центральное · 2P	Глубина, дверь в нише · Центральное · 2P
630 kg	2	Один	1 750	1 975	1 800	1 750	1 740	1 700
630 kg	2	Проходная	1 750	1 975	2 040	1 940	1 920	1 880
630 kg	2,5	Один	1 750	1 975	1 800	1 750	1 740	1 700
630 kg	2,5	Проходная	1 750	1 975	2 040	1 940	1 920	1 880
800 kg	2	Один	1 990	2 150	1 800	1 750	1 740	1 700
800 kg	2	Проходная	1 990	2 150	2 040	1 940	1 920	1 880
800 kg	2,5	Один	1 990	2 150	1 800	1 750	1 740	1 700
800 kg	2,5	Проходная	1 990	2 150	2 040	1 940	1 920	1 880
1.000 kg (depth)	2	Один	1 750	2 000	2 500	2 450	2 450	2 410
1.000 kg (depth)	2	Проходная	1 750	2 000	2 750	2 640	2 640	2 600
1.000 kg (depth)	2,5	Один	1 750	2 000	2 500	2 450	2 450	2 410
1.000 kg (depth)	2,5	Проходная	1 750	2 000	2 750	2 640	2 640	2 600
1.000 kg (wide)	2	Один	2 150	2 250	1 800	1 750	1 750	1 710
1.000 kg (wide)	2	Проходная	2 150	2 250	2 050	1 940	1 940	1 890
1.000 kg (wide)	2,5	Один	2 250	2 250	1 800	1 750	1 750	1 710
1.000 kg (wide)	2,5	Проходная	2 250	2 250	2 050	1 940	1 940	1 890

Номинальная грузоподъёмность	Скорость	Входы	Ширина · Боковое · 2P	Ширина · Центральное · 2P	Глубина, дверь внутри шахты · Боковое · 2P	Глубина, дверь в нише · Боковое · 2P	Глубина, дверь внутри шахты · Центральное · 2P	Глубина, дверь в нише · Центральное · 2P
1.250kg	1	Один	1 750	1 975	2 700	2 650	2 650	2 600
1.250kg	1	Проходная	1 750	1 975	2 950	2 840	2 825	2 740
1.250kg	1,6	Один	1 750	1 975	2 700	2 650	2 650	2 600
1.250kg	1,6	Проходная	1 750	1 975	2 950	2 840	2 825	2 740
1.600kg	1	Один	2 290	2 380	2 800	2 760	2 750	2 710
1.600kg	1	Проходная	2 290	2 380	3 050	2 950	2 930	2 850
1.600kg	1,6	Один	2 290	2 380	2 800	2 760	2 750	2 710
1.600kg	1,6	Проходная	2 290	2 380	3 050	2 950	2 930	2 850
2.000kg	1	Один	2 420	3 000	3 100	3 050	3 050	3 000
2.000kg	1	Проходная	2 420	3 000	3 340	3 250	3 220	3 100
2.000kg	1,6	Один	2 420	3 000	3 100	3 050	3 050	3 000
2.000kg	1,6	Проходная	2 420	3 000	3 340	3 250	3 220	3 100
2.500kg	1	Один	2 480	2 975	3 100	3 050	3 050	3 000
2.500kg	1	Проходная	2 480	2 975	3 340	3 250	3 220	3 100
2.500kg	1,6	Один	2 480	2 975	3 100	3 050	3 050	3 000
2.500kg	1,6	Проходная	2 480	2 975	3 340	3 250	3 220	3 100

Номинальная грузоподъёмность	Скорость	Входы	Ширина · Боковое · 2P	Ширина · Центральное · 2P	Глубина, дверь внутри шахты · Боковое · 2P	Глубина, дверь в нише · Боковое · 2P	Глубина, дверь внутри шахты · Центральное · 2P	Глубина, дверь в нише · Центральное · 2P
1.250kg	2	Один	1 850	2 035	2 700	2 650	2 650	2 600
1.250kg	2	Проходная	1 850	2 035	2 950	2 840	2 825	2 740
1.250kg	2,5	Один	1 850	2 035	2 700	2 650	2 650	2 600
1.250kg	2,5	Проходная	1 850	2 035	2 950	2 840	2 825	2 740
1.600kg	2	Один	2 325	2 380	2 800	2 760	2 750	2 710
1.600kg	2	Проходная	2 325	2 380	3 050	2 950	2 930	2 850
1.600kg	2,5	Один	2 325	2 380	2 800	2 760	2 750	2 710
1.600kg	2,5	Проходная	2 325	2 380	3 050	2 950	2 930	2 850
2.000kg	2	Один	2 425	3 000	3 100	3 050	3 050	3 000
2.000kg	2	Проходная	2 425	3 000	3 340	3 250	3 220	3 100
2.000kg	2,5	Один	2 425	3 000	3 100	3 050	3 050	3 000
2.000kg	2,5	Проходная	2 425	3 000	3 340	3 250	3 220	3 100
2.500kg	2	Один	2 500	3 000	3 100	3 050	3 050	3 000
2.500kg	2	Проходная	2 500	3 000	3 340	3 250	3 220	3 100
2.500kg	2,5	Один	2 500	3 000	3 100	3 050	3 050	3 000
2.500kg	2,5	Проходная	2 500	3 000	3 340	3 250	3 220	3 100

Номинальная грузоподъёмность	Скорость	Входы	Ширина · Центральное · 4P	Глубина, дверь внутри шахты · Центральное · 4P	Глубина, дверь в нише · Центральное · 4P
3.000kg	1	Один	2 750	3 220	3 170
3.000kg	1	Проходная	2 750	3 440	3 340
3.000kg	1,6	Один	2 750	3 220	3 170
3.000kg	1,6	Проходная	2 750	3 440	3 340
3.500kg	1	Один	2 850	3 470	3 420
3.500kg	1	Проходная	2 850	3 690	3 590
3.500kg	1,6	Один	2 850	3 470	3 420
3.500kg	1,6	Проходная	2 850	3 690	3 590
4.000kg	1	Один	3 150	3 320	3 270
4.000kg	1	Проходная	3 150	3 540	3 440
4.000kg	1,6	Один	3 150	3 320	3 270
4.000kg	1,6	Проходная	3 150	3 540	3 440
5.000kg	1	Один	3 750	3 670	3 620
5.000kg	1	Проходная	3 750	3 890	3 790

Оборудование и опции

Standard	XP100	XP125	XP200	XP225	XP500
EN81-20 / 50	●	●	●	●	●
EN81-28	●	●	●	●	●
EN81-58	●	●	●	●	●
EN81-70	○	○	○	○	○
EN81-71	○	○	○	○	○
Cat.0	○	○	○	○	○
Cat.1	○	○	○	○	○
Cat.2	○	○	○	○	○
EN81-72	○	○	○	○	○
EN81-73	●	●	●	●	●
EN81-77	○	○	○	○	○
Cat.1	○	○	○	○	○
Cat.2	○	○	○	○	○
Cat.3	○	○	○	○	○
EN12015 - EN12016	○	○	○	○	○

Suspension Model	XP100	XP125	XP200	XP225	XP500
Suspension 1:1	○	–	–	–	–
Suspension 2:1	●	●	●	●	–
Suspension 4:1	–	–	○	–	●

Traction Machine	XP100	XP125	XP200	XP225	XP500
Machine Ziehl Abegg	●	●	●	●	●
Machine Alberto Sassi	○	○	○	○	○
Machine WITTUR	○	○	○	○	○
Machine TORIN	–	–	–	–	–

Inverter	XP100	XP125	XP200	XP225	XP500
Inverter ZetaDyn	○	○	○	○	○
Inverter ARKEL	●	●	●	●	●
Inverter YASKAWA	○	○	○	○	○

Controller	XP100	XP125	XP200	XP225	XP500
ARKEL ARCODE Controller	●	●	●	●	●
LISA 20 Contreller	○	○	○	○	○

Safety Gear	XP100	XP125	XP200	XP225	XP500
Safety Gear Wittur	●	●	●	●	●
Safety Gear Kobianchi	○	○	○	○	○
Safety Gear Dynatech	○	○	○	○	○

Cabin Walls Structure	XP100	XP125	XP200	XP225	XP500
Cabin wall panels (single leaf) [only for powder coating]	○	○	○	○	○
Cabin wall panels (twin leaf)	●	●	●	●	●
Cabin wall panels (twin leaf - MDF supported)	○	○	○	○	○
Cabin wall panels (twin leaf - Isolution pad)	○	○	○	●	●

Cabin Walls Decoration	XP100	XP125	XP200	XP225	XP500
Powder Coated RAL 9006 White Aluminium Walls	●	●	●	●	●
Powder Coated RAL 9016 Trafic White Walls	●	●	●	●	●
Powder Coated RAL 7032 Pebble Grey Walls	●	●	●	●	●
Stainless Steel Satin AISI304	○	○	○	○	○
Stainless Steel Linen AISI304	○	○	○	○	○
Stainless Steel Diamond AISI304	○	○	○	○	○
Stainless Steel Leather AISI304	○	○	○	○	○
Stainless Steel Mirror AISI304	○	○	○	○	○
Coloured Stainless Steel [Bronze, Gold, Champaign, Black]	○	○	○	○	○
Coloured Laminated Glass [White, Blue, Green, Red]	○	○	○	○	–
Decorative MDF with various colours	○	○	○	○	–
Stainless Steel - MESH Combination	○	○	○	○	○
Rear Wall Panoramic	○	○	○	○	–
2 walls panoramic	○	○	○	○	–
3 walls panoramic	○	○	○	○	–

Cabin Equipment	XP100	XP125	XP200	XP225	XP500
Car ceiling	●	●	●	●	●
False Ceiling (AISI 304 or other cladding) LED Lighting	○	○	○	○	○
Car ventilation - indirect - invisible	○	○	○	○	○
Car ventilation with on/off button	○	○	○	○	○
Handrail on rear wall	●	●	●	●	●
Handrail on rear + side walls	○	○	○	○	○
Handrail on all walls	○	○	○	○	○
Bumper (MDF)	○	○	○	○	●
Bumper (Stainless Steel)	○	○	○	○	○

Door Supplier / Model	XP100	XP125	XP200	XP225	XP500
Fermator Elite	○	○	–	–	–
Fermator MEGA	○	○	○	○	○
Fermator Premium	○	○	○	○	○
Wittur Augusto	●	●	–	–	–
Wittur Hydra	○	○	●	●	○
Wittur Pegasus	○	○	○	○	○

Door Options	XP100	XP125	XP200	XP225	XP500
EN81-58 E120 Fire Rated	●	●	●	●	●
EN81-58 EI60 Fire Rated	○	○	○	○	○
EN81-71 Antivandal	○	○	○	○	○
Heavy Duty Goods Elevator Door	–	–	○	–	○
IP54 Protection	○	○	○	○	○
IPX3 Protection	○	○	○	○	○
2 Panel Side Opening	●	●	●	●	–
2 Panel Central Opening	●	●	●	●	–
3 Panel Side Opening	○	●	○	●	–
4 Panel Central Opening	○	○	○	○	○
6 Panel Central Opening	○	○	○	○	○
Framed Glass Door (EN81-58 E60)	○	○	○	○	–
Full Glass (None E Certificate)	○	○	○	○	–
Round Glass	○	–	○	–	–
Aluminium Sill	●	●	●	●	–
Reinforced Aluminium Sill	○	○	○	○	●
Steel Sill	○	○	○	○	○
Reinforced Steel Sill	○	○	○	○	○

Door Closing	XP100	XP125	XP200	XP225	XP500
Spring	●	●	●	●	–
Spring / Counterweight	○	○	○	○	○

Controller Function	XP100	XP125	XP200	XP225	XP500
Regenative Inverter	○	○	○	○	○
Halogen Free wiring	○	○	○	○	○
Group Control Up to 32 Lift	●	●	●	●	●
Control Box (Surface Mounted)	●	●	●	●	●
Control Box (In wall)	●	●	●	●	●
Slim Control Box (Splited parts will be in shaft)	○	○	○	○	○
Control Box in Top Landing	●	●	●	●	●
Control Box removed from shaft up to 3m	○	○	○	○	○
Control Box in any landing	○	○	○	○	○
Automatic Rescue Device to the nearest landing	●	●	●	●	●
Automatic Rescue Device to any landing	○	○	○	○	○
Generator connection	○	○	○	○	○
Service Hour Meter	○	○	○	○	○
Trip Meter	○	○	○	○	○
5 way Intercom with GSM Module	○	○	○	○	○
Advance Door Opening	○	○	○	○	○
Relevelling	○	○	○	○	○
Door nudging with audience signal	○	○	○	○	○

● Стандарт ○ Опция – не указано

Важное примечание

Данные каталога являются ориентировочной информацией для проектирования и не являются обязательством. Перед использованием этих значений в спецификации или проекте шахты получите подтверждение от инженерного отдела.