

BRONZE LIFT

FACT SHEET

XS Series

Our XS Series elevator models offers a perfect balance of performance and value, ideal for a variety of commercial and residential settings..

Capacity and car dimensions

The table scrolls sideways. All dimensions in millimetres unless stated otherwise.

100

Rated load	Persons	Speed	Max. travel	Max. stops	Entrances	Car Width	Car Depth	Car Height	Car weight	Door Width	Door Height	Headroom	Pit	Min. floor distance
450 kg	6	1	40	16	Single	1,000	1,250	2100 – 2700	900	800 – 1000	2000 – 2500	3,300	1,100	2,700
450 kg	6	1	40	16	Double	1,000	1,250	2100 – 2700	900	800 – 1000	2000 – 2500	3,300	1,100	2,700
450 kg	6	1.6	60	21	Single	1,000	1,250	2100 – 2700	900	800 – 1000	2000 – 2500	3,600	1,400	2,700
450 kg	6	1.6	60	21	Double	1,000	1,250	2100 – 2700	900	800 – 1000	2000 – 2500	3,600	1,400	2,700
630 kg	8	1	40	16	Single	1,100	1,400	2100 – 2700	1,200	800 – 1100	2000 – 2500	3,300	1,100	2,700
630 kg	8	1	40	16	Double	1,100	1,400	2100 – 2700	1,200	800 – 1100	2000 – 2500	3,300	1,100	2,700
630 kg	8	1.6	60	21	Single	1,100	1,400	2100 – 2700	1,200	800 – 1100	2000 – 2500	3,600	1,400	2,700
630 kg	8	1.6	60	21	Double	1,100	1,400	2100 – 2700	1,200	800 – 1100	2000 – 2500	3,600	1,400	2,700
800 kg	10	1	40	16	Single	1,350	1,400	2100 – 2700	1,500	800 – 1100	2000 – 2500	3,300	1,100	2,700
800 kg	10	1	40	16	Double	1,350	1,400	2100 – 2700	1,500	800 – 1100	2000 – 2500	3,300	1,100	2,700
800 kg	10	1.6	60	21	Single	1,350	1,400	2100 – 2700	1,500	800 – 1100	2000 – 2500	3,600	1,400	2,700
800 kg	10	1.6	60	21	Double	1,350	1,400	2100 – 2700	1,500	800 – 1100	2000 – 2500	3,600	1,400	2,700
1.000 kg (depth)	13	1	40	16	Single	1,100	2,100	2100 – 2700	1,800	800 – 1100	2000 – 2500	3,300	1,100	2,700
1.000 kg (depth)	13	1	40	16	Double	1,100	2,100	2100 – 2700	1,800	800 – 1100	2000 – 2500	3,300	1,100	2,700
1.000 kg (depth)	13	1.6	60	21	Single	1,100	2,100	2100 – 2700	1,800	800 – 1100	2000 – 2500	3,600	1,400	2,700
1.000 kg (depth)	13	1.6	60	21	Double	1,100	2,100	2100 – 2700	1,800	800 – 1100	2000 – 2500	3,600	1,400	2,700
1.000 kg (wide)	13	1	40	16	Single	1,600	1,400	2100 – 2700	1,800	800 – 1300	2000 – 2500	3,300	1,100	2,700
1.000 kg (wide)	13	1	40	16	Double	1,600	1,400	2100 – 2700	1,800	800 – 1300	2000 – 2500	3,300	1,100	2,700
1.000 kg (wide)	13	1.6	60	21	Single	1,600	1,400	2100 – 2700	1,800	800 – 1300	2000 – 2500	3,600	1,400	2,700
1.000 kg (wide)	13	1.6	60	21	Double	1,600	1,400	2100 – 2700	1,800	800 – 1300	2000 – 2500	3,600	1,400	2,700

Rated load	Persons	Speed	Max. travel	Max. stops	Entrances	Car Width	Car Depth	Car Height	Car weight	Door Width	Door Height	Headroom	Pit	Min. floor distance
630 kg	8	2	80	30	Single	1,100	1,400	2100 – 2700	1,200	800 – 1100	2000 – 2500	4,100	1,500	2,700
630 kg	8	2	80	30	Double	1,100	1,400	2100 – 2700	1,200	800 – 1100	2000 – 2500	4,100	1,500	2,700
630 kg	8	2.5	120	40	Single	1,100	1,400	2100 – 2700	1,200	800 – 1100	2000 – 2500	4,400	1,950	2,700
630 kg	8	2.5	120	40	Double	1,100	1,400	2100 – 2700	1,200	800 – 1100	2000 – 2500	4,400	1,950	2,700
800 kg	10	2	80	30	Single	1,350	1,400	2100 – 2700	1,500	800 – 1100	2000 – 2500	4,100	1,500	2,700
800 kg	10	2	80	30	Double	1,350	1,400	2100 – 2700	1,500	800 – 1100	2000 – 2500	4,100	1,500	2,700
800 kg	10	2.5	120	40	Single	1,350	1,400	2100 – 2700	1,500	800 – 1100	2000 – 2500	4,400	1,950	2,700
800 kg	10	2.5	120	40	Double	1,350	1,400	2100 – 2700	1,500	800 – 1100	2000 – 2500	4,400	1,950	2,700
1.000 kg (depth)	13	2	80	30	Single	1,100	2,100	2100 – 2700	1,800	800 – 1100	2000 – 2500	4,100	1,500	2,700
1.000 kg (depth)	13	2	80	30	Double	1,100	2,100	2100 – 2700	1,800	800 – 1100	2000 – 2500	4,100	1,500	2,700
1.000 kg (depth)	13	2.5	120	40	Single	1,100	2,100	2100 – 2700	1,800	800 – 1100	2000 – 2500	4,400	1,950	2,700
1.000 kg (depth)	13	2.5	120	40	Double	1,100	2,100	2100 – 2700	1,800	800 – 1100	2000 – 2500	4,400	1,950	2,700
1.000 kg (wide)	13	2	80	30	Single	1,600	1,400	2100 – 2700	1,800	800 – 1300	2000 – 2500	4,100	1,500	2,700
1.000 kg (wide)	13	2	80	30	Double	1,600	1,400	2100 – 2700	1,800	800 – 1300	2000 – 2500	4,100	1,500	2,700
1.000 kg (wide)	13	2.5	120	40	Single	1,600	1,400	2100 – 2700	1,800	800 – 1300	2000 – 2500	4,400	1,950	2,700
1.000 kg (wide)	13	2.5	120	40	Double	1,600	1,400	2100 – 2700	1,800	800 – 1300	2000 – 2500	4,400	1,950	2,700

Rated load	Persons	Speed	Max. travel	Max. stops	Entrances	Car Width	Car Depth	Car Height	Car weight	Door Width	Door Height	Headroom	Pit	Min. floor distance
1.250kg	16	1	40	16	Single	1,200	2,300	2100 – 2700	2,000	900 – 1100	2000 – 2500	3,500	1,250	2,700
1.250kg	16	1	40	16	Double	1,200	2,300	2100 – 2700	2,000	900 – 1100	2000 – 2500	3,500	1,250	2,700
1.250kg	16	1.6	80	21	Single	1,200	2,300	2100 – 2700	2,000	900 – 1100	2000 – 2500	3,750	1,500	2,700
1.250kg	16	1.6	80	21	Double	1,200	2,300	2100 – 2700	2,000	900 – 1100	2000 – 2500	3,750	1,500	2,700
1.600kg	20	1	40	16	Single	1,400	2,400	2100 – 2700	2,200	900 – 1300	2000 – 2500	3,500	1,250	2,700
1.600kg	20	1	40	16	Double	1,400	2,400	2100 – 2700	2,200	900 – 1300	2000 – 2500	3,500	1,250	2,700
1.600kg	20	1.6	80	21	Single	1,400	2,400	2100 – 2700	2,200	900 – 1300	2000 – 2500	3,750	1,500	2,700
1.600kg	20	1.6	80	21	Double	1,400	2,400	2100 – 2700	2,200	900 – 1300	2000 – 2500	3,750	1,500	2,700
2.000kg	26	1	40	16	Single	1,500	2,700	2100 – 2700	2,600	1000 – 1400	2000 – 2500	3,750	1,350	2,700
2.000kg	26	1	40	16	Double	1,500	2,700	2100 – 2700	2,600	1000 – 1400	2000 – 2500	3,750	1,350	2,700
2.000kg	26	1.6	80	21	Single	1,500	2,700	2100 – 2700	2,600	1000 – 1400	2000 – 2500	4,000	1,600	2,700
2.000kg	26	1.6	80	21	Double	1,500	2,700	2100 – 2700	2,600	1000 – 1400	2000 – 2500	4,000	1,600	2,700
2.500kg	33	1	40	16	Single	1,800	2,700	2100 – 2700	3,000	1000 – 1400	2000 – 2500	3,750	1,350	2,700
2.500kg	33	1	40	16	Double	1,800	2,700	2100 – 2700	3,000	1000 – 1400	2000 – 2500	3,750	1,350	2,700
2.500kg	33	1.6	80	21	Single	1,800	2,700	2100 – 2700	3,000	1000 – 1400	2000 – 2500	4,000	1,600	2,700
2.500kg	33	1.6	80	21	Double	1,800	2,700	2100 – 2700	3,000	1000 – 1400	2000 – 2500	4,000	1,600	2,700

Rated load	Persons	Speed	Max. travel	Max. stops	Entrances	Car Width	Car Depth	Car Height	Car weight	Door Width	Door Height	Headroom	Pit	Min. floor distance
1.250kg	16	2	80	30	Single	1,200	2,300	2100 – 2700	2,000	900 – 1100	2000 – 2500	4,250	1,600	2,700
1.250kg	16	2	80	30	Double	1,200	2,300	2100 – 2700	2,000	900 – 1100	2000 – 2500	4,250	1,600	2,700
1.250kg	16	2.5	120	40	Single	1,200	2,300	2100 – 2700	2,000	900 – 1100	2000 – 2500	4,500	2,050	2,700
1.250kg	16	2.5	120	40	Double	1,200	2,300	2100 – 2700	2,000	900 – 1100	2000 – 2500	4,500	2,050	2,700
1.600kg	20	2	80	30	Single	1,400	2,400	2100 – 2700	2,200	900 – 1300	2000 – 2500	4,250	1,600	2,700
1.600kg	20	2	80	30	Double	1,400	2,400	2100 – 2700	2,200	900 – 1300	2000 – 2500	4,250	1,600	2,700
1.600kg	20	2.5	120	40	Single	1,400	2,400	2100 – 2700	2,200	900 – 1300	2000 – 2500	4,500	2,050	2,700
1.600kg	20	2.5	120	40	Double	1,400	2,400	2100 – 2700	2,200	900 – 1300	2000 – 2500	4,500	2,050	2,700
2.000kg	26	2	80	30	Single	1,500	2,700	2100 – 2700	2,600	1000 – 1400	2000 – 2500	4,400	1,750	2,700
2.000kg	26	2	80	30	Double	1,500	2,700	2100 – 2700	2,600	1000 – 1400	2000 – 2500	4,400	1,750	2,700
2.000kg	26	2.5	120	40	Single	1,500	2,700	2100 – 2700	2,600	1000 – 1400	2000 – 2500	4,700	2,250	2,700
2.000kg	26	2.5	120	40	Double	1,500	2,700	2100 – 2700	2,600	1000 – 1400	2000 – 2500	4,700	2,250	2,700
2.500kg	33	2	80	30	Single	1,800	2,700	2100 – 2700	3,000	1000 – 1400	2000 – 2500	4,400	1,750	2,700
2.500kg	33	2	80	30	Double	1,800	2,700	2100 – 2700	3,000	1000 – 1400	2000 – 2500	4,400	1,750	2,700
2.500kg	33	2.5	120	40	Single	1,800	2,700	2100 – 2700	3,000	1000 – 1400	2000 – 2500	4,700	2,250	2,700
2.500kg	33	2.5	120	40	Double	1,800	2,700	2100 – 2700	3,000	1000 – 1400	2000 – 2500	4,700	2,250	2,700

Rated load	Persons	Speed	Max. travel	Max. stops	Entrances	Car Width	Car Depth	Car Height	Car weight	Door Width	Door Height	Headroom	Pit	Min. floor distance
3.000kg	40	1	40	16	Single	2,000	2,800	2100 – 2700	3,500	1400 – 2000	2000 – 2500	3,900	1,600	2,700
3.000kg	40	1	40	16	Double	2,000	2,800	2100 – 2700	3,500	1400 – 2000	2000 – 2500	3,900	1,600	2,700
3.000kg	40	1.6	60	20	Single	2,000	2,800	2100 – 2700	3,500	1400 – 2000	2000 – 2500	4,200	1,800	2,700
3.000kg	40	1.6	60	20	Double	2,000	2,800	2100 – 2700	3,500	1400 – 2000	2000 – 2500	4,200	1,800	2,700
3.500kg	46	1	40	16	Single	2,100	3,050	2100 – 2700	3,500	1400 – 2000	2000 – 2500	3,900	1,600	2,700
3.500kg	46	1	40	16	Double	2,100	3,050	2100 – 2700	3,500	1400 – 2000	2000 – 2500	3,900	1,600	2,700
3.500kg	46	1.6	60	20	Single	2,100	3,050	2100 – 2700	3,500	1400 – 2000	2000 – 2500	4,200	1,800	2,700
3.500kg	46	1.6	60	20	Double	2,100	3,050	2100 – 2700	3,500	1400 – 2000	2000 – 2500	4,200	1,800	2,700
4.000kg	53	1	40	16	Single	2,400	2,900	2100 – 2700	3,500	1400 – 2000	2000 – 2500	3,900	1,600	2,700
4.000kg	53	1	40	16	Double	2,400	2,900	2100 – 2700	3,500	1400 – 2000	2000 – 2500	3,900	1,600	2,700
4.000kg	53	1.6	60	20	Single	2,400	2,900	2100 – 2700	3,500	1400 – 2000	2000 – 2500	4,200	1,800	2,700
4.000kg	53	1.6	60	20	Double	2,400	2,900	2100 – 2700	3,500	1400 – 2000	2000 – 2500	4,200	1,800	2,700
5.000kg	65	1	40	16	Single	3,000	3,250	2100 – 2700	3,500	1400 – 2000	2000 – 2500	4,200	1,800	2,700
5.000kg	65	1	40	16	Double	3,000	3,250	2100 – 2700	3,500	1400 – 2000	2000 – 2500	4,200	1,800	2,700

Shaft dimensions

Rated load	Speed	Entrances	Width · Side · 2P	Width · Centre · 2P	Depth, door inside shaft · Side · 2P	Depth, door in recess · Side · 2P	Depth, door inside shaft · Centre · 2P	Depth, door in recess · Centre · 2P
450 kg	1	Single	1,520	1,750	1,650	1,595	1,590	1,550
450 kg	1	Double	1,520	1,750	1,890	1,780	1,770	1,730
450 kg	1.6	Single	1,520	1,750	1,650	1,595	1,590	1,550
450 kg	1.6	Double	1,520	1,750	1,890	1,780	1,770	1,730
630 kg	1	Single	1,620	1,970	1,800	1,750	1,740	1,700
630 kg	1	Double	1,620	1,970	2,040	1,940	1,920	1,880
630 kg	1.6	Single	1,620	1,970	1,800	1,750	1,740	1,700
630 kg	1.6	Double	1,620	1,970	2,040	1,940	1,920	1,880
800 kg	1	Single	1,850	2,100	1,800	1,750	1,740	1,700
800 kg	1	Double	1,850	2,100	2,040	1,940	1,920	1,880
800 kg	1.6	Single	1,850	2,100	1,800	1,750	1,740	1,700
800 kg	1.6	Double	1,850	2,100	2,040	1,940	1,920	1,880
1.000 kg (depth)	1	Single	1,620	1,970	2,500	2,445	2,450	2,410
1.000 kg (depth)	1	Double	1,620	1,970	2,740	2,630	2,640	2,600
1.000 kg (depth)	1.6	Single	1,620	1,970	2,500	2,445	2,450	2,410
1.000 kg (depth)	1.6	Double	1,620	1,970	2,740	2,630	2,640	2,600
1.000 kg (wide)	1	Single	2,120	2,150	1,800	1,750	1,740	1,700
1.000 kg (wide)	1	Double	2,120	2,150	2,040	1,940	1,920	1,880
1.000 kg (wide)	1.6	Single	2,120	2,150	1,800	1,750	1,740	1,700
1.000 kg (wide)	1.6	Double	2,120	2,150	2,040	1,940	1,920	1,880

Rated load	Speed	Entrances	Width · Side · 2P	Width · Centre · 2P	Depth, door inside shaft · Side · 2P	Depth, door in recess · Side · 2P	Depth, door inside shaft · Centre · 2P	Depth, door in recess · Centre · 2P
630 kg	2	Single	1,750	1,975	1,800	1,750	1,740	1,700
630 kg	2	Double	1,750	1,975	2,040	1,940	1,920	1,880
630 kg	2.5	Single	1,750	1,975	1,800	1,750	1,740	1,700
630 kg	2.5	Double	1,750	1,975	2,040	1,940	1,920	1,880
800 kg	2	Single	1,990	2,150	1,800	1,750	1,740	1,700
800 kg	2	Double	1,990	2,150	2,040	1,940	1,920	1,880
800 kg	2.5	Single	1,990	2,150	1,800	1,750	1,740	1,700
800 kg	2.5	Double	1,990	2,150	2,040	1,940	1,920	1,880
1.000 kg (depth)	2	Single	1,750	2,000	2,500	2,450	2,450	2,410
1.000 kg (depth)	2	Double	1,750	2,000	2,750	2,640	2,640	2,600
1.000 kg (depth)	2.5	Single	1,750	2,000	2,500	2,450	2,450	2,410
1.000 kg (depth)	2.5	Double	1,750	2,000	2,750	2,640	2,640	2,600
1.000 kg (wide)	2	Single	2,150	2,250	1,800	1,750	1,750	1,710
1.000 kg (wide)	2	Double	2,150	2,250	2,050	1,940	1,940	1,890
1.000 kg (wide)	2.5	Single	2,250	2,250	1,800	1,750	1,750	1,710
1.000 kg (wide)	2.5	Double	2,250	2,250	2,050	1,940	1,940	1,890

Rated load	Speed	Entrances	Width · Side · 2P	Width · Centre · 2P	Depth, door inside shaft · Side · 2P	Depth, door in recess · Side · 2P	Depth, door inside shaft · Centre · 2P	Depth, door in recess · Centre · 2P
1.250kg	1	Single	1,750	1,975	2,700	2,650	2,650	2,600
1.250kg	1	Double	1,750	1,975	2,950	2,840	2,825	2,740
1.250kg	1.6	Single	1,750	1,975	2,700	2,650	2,650	2,600
1.250kg	1.6	Double	1,750	1,975	2,950	2,840	2,825	2,740
1.600kg	1	Single	2,290	2,380	2,800	2,760	2,750	2,710
1.600kg	1	Double	2,290	2,380	3,050	2,950	2,930	2,850
1.600kg	1.6	Single	2,290	2,380	2,800	2,760	2,750	2,710
1.600kg	1.6	Double	2,290	2,380	3,050	2,950	2,930	2,850
2.000kg	1	Single	2,420	3,000	3,100	3,050	3,050	3,000
2.000kg	1	Double	2,420	3,000	3,340	3,250	3,220	3,100
2.000kg	1.6	Single	2,420	3,000	3,100	3,050	3,050	3,000
2.000kg	1.6	Double	2,420	3,000	3,340	3,250	3,220	3,100
2.500kg	1	Single	2,480	2,975	3,100	3,050	3,050	3,000
2.500kg	1	Double	2,480	2,975	3,340	3,250	3,220	3,100
2.500kg	1.6	Single	2,480	2,975	3,100	3,050	3,050	3,000
2.500kg	1.6	Double	2,480	2,975	3,340	3,250	3,220	3,100

Rated load	Speed	Entrances	Width · Side · 2P	Width · Centre · 2P	Depth, door inside shaft · Side · 2P	Depth, door in recess · Side · 2P	Depth, door inside shaft · Centre · 2P	Depth, door in recess · Centre · 2P
1.250kg	2	Single	1,850	2,035	2,700	2,650	2,650	2,600
1.250kg	2	Double	1,850	2,035	2,950	2,840	2,825	2,740
1.250kg	2.5	Single	1,850	2,035	2,700	2,650	2,650	2,600
1.250kg	2.5	Double	1,850	2,035	2,950	2,840	2,825	2,740
1.600kg	2	Single	2,325	2,380	2,800	2,760	2,750	2,710
1.600kg	2	Double	2,325	2,380	3,050	2,950	2,930	2,850
1.600kg	2.5	Single	2,325	2,380	2,800	2,760	2,750	2,710
1.600kg	2.5	Double	2,325	2,380	3,050	2,950	2,930	2,850
2.000kg	2	Single	2,425	3,000	3,100	3,050	3,050	3,000
2.000kg	2	Double	2,425	3,000	3,340	3,250	3,220	3,100
2.000kg	2.5	Single	2,425	3,000	3,100	3,050	3,050	3,000
2.000kg	2.5	Double	2,425	3,000	3,340	3,250	3,220	3,100
2.500kg	2	Single	2,500	3,000	3,100	3,050	3,050	3,000
2.500kg	2	Double	2,500	3,000	3,340	3,250	3,220	3,100
2.500kg	2.5	Single	2,500	3,000	3,100	3,050	3,050	3,000
2.500kg	2.5	Double	2,500	3,000	3,340	3,250	3,220	3,100

Rated load	Speed	Entrances	Width · Centre · 4P	Depth, door inside shaft · Centre · 4P	Depth, door in recess · Centre · 4P
3.000kg	1	Single	2,750	3,220	3,170
3.000kg	1	Double	2,750	3,440	3,340
3.000kg	1.6	Single	2,750	3,220	3,170
3.000kg	1.6	Double	2,750	3,440	3,340
3.500kg	1	Single	2,850	3,470	3,420
3.500kg	1	Double	2,850	3,690	3,590
3.500kg	1.6	Single	2,850	3,470	3,420
3.500kg	1.6	Double	2,850	3,690	3,590
4.000kg	1	Single	3,150	3,320	3,270
4.000kg	1	Double	3,150	3,540	3,440
4.000kg	1.6	Single	3,150	3,320	3,270
4.000kg	1.6	Double	3,150	3,540	3,440
5.000kg	1	Single	3,750	3,670	3,620
5.000kg	1	Double	3,750	3,890	3,790

Equipment and options

Standard	XS100	XS125	XS200	XS225	XS500
EN81-20 / 50	●	●	●	●	●
EN81-28	●	●	●	●	●
EN81-58	●	●	●	●	●
EN81-70	○	○	○	○	○
EN81-71	○	○	○	○	○
Cat.0	○	○	○	○	○
Cat.1	○	○	○	○	○
Cat.2	○	○	○	○	○
EN81-72	○	○	○	○	○
EN81-73	●	●	●	●	●
EN81-77	○	○	○	○	○
Cat.1	○	○	○	○	○
Cat.2	○	○	○	○	○
Cat.3	○	○	○	○	○
EN12015 - EN12016	○	○	○	○	○
Suspension Model	XS100	XS125	XS200	XS225	XS500
Suspension 1:1	○	—	—	—	—
Suspension 2:1	●	●	●	●	—
Suspension 4:1	—	—	○	—	●
Traction Machine	XS100	XS125	XS200	XS225	XS500
Machine Ziehl Abegg	○	○	○	○	○
Machine Alberto Sassi	○	○	○	○	○
Machine WITTUR	○	○	○	○	○
Machine TORIN	●	●	●	●	●
Inverter	XS100	XS125	XS200	XS225	XS500
Inverter ZetaDyn	○	○	○	○	○
Inverter ARKEL	●	●	●	●	●
Inverter YASKAWA	○	○	○	○	○

Controller	XS100	XS125	XS200	XS225	XS500
ARKEL ARCODE Controller	●	●	●	●	●
LISA 20 Contreller	○	○	○	○	○
Safety Gear	XS100	XS125	XS200	XS225	XS500
Safety Gear Wittur	○	○	○	○	○
Safety Gear Kobianchi	○	○	○	○	○
Safety Gear Dynatech	●	●	●	●	●
Cabin Walls Structure	XS100	XS125	XS200	XS225	XS500
Cabin wall panels (single leaf) [only for powder coating]	○	○	○	○	○
Cabin wall panels (twin leaf)	●	●	●	●	●
Cabin wall panels (twin leaf - MDF supported)	○	○	○	○	○
Cabin wall panels (twin leaf - Isolution pad)	○	○	○	●	○
Cabin Walls Decoration	XS100	XS125	XS200	XS225	XS500
Powder Coated RAL 9006 White Aluminium Walls	●	●	●	●	●
Powder Coated RAL 9016 Trafic White Walls	●	●	●	●	●
Powder Coated RAL 7032 Pebble Grey Walls	●	●	●	●	●
Stainless Steel Satin AISI304	○	○	○	○	○
Stainless Steel Linen AISI304	○	○	○	○	○
Stainless Steel Diamond AISI304	○	○	○	○	○
Stainless Steel Leather AISI304	○	○	○	○	○
Stainless Steel Mirror AISI304	○	○	○	○	○
Coloured Stainless Steel [Bronze, Gold, Champaign, Black]	○	○	○	○	○
Coloured Laminated Glass [White, Blue, Green, Red]	○	○	○	○	—
Decorative MDF with various colours	○	○	○	○	—
Stainless Steel - MESH Combination	○	○	○	○	○
Rear Wall Panoramic	○	○	○	○	—
2 walls panoramic	○	○	○	○	—
3 walls panoramic	○	○	○	○	—

Cabin Equipment	XS100	XS125	XS200	XS225	XS500
Car ceiling	●	●	●	●	●
False Ceiling (AISI 304 or other cladding) LED Lighting	○	○	○	○	○
Car ventilation - indirect - invisible	○	○	○	○	○
Car ventilation with on/off button	○	○	○	○	○
Handrail on rear wall	●	●	●	●	●
Handrail on rear + side walls	○	○	○	○	○
Handrail on all walls	○	○	○	○	○
Bumper (MDF)	○	○	○	○	●
Bumper (Stainless Steel)	○	○	○	○	○

Door Supplier / Model	XS100	XS125	XS200	XS225	XS500
Fermator Elite	●	●	—	—	—
Fermator MEGA	○	○	●	●	○
Fermator Premium	○	○	○	○	○
Wittur Augusto	○	○	—	—	—
Wittur Hydra	○	○	○	○	○
Wittur Pegasus	○	○	○	○	○

Door Options	XS100	XS125	XS200	XS225	XS500
EN81-58 E120 Fire Rated	●	●	●	●	●
EN81-58 EI60 Fire Rated	○	○	○	○	○
EN81-71 Antivandal	○	○	○	○	○
Heavy Duty Goods Elevator Door	—	—	○	—	○
IP54 Protection	○	○	○	○	○
IPX3 Protection	○	○	○	○	○
2 Panel Side Opening	●	●	●	●	—
2 Panel Central Opening	●	●	●	●	—
3 Panel Side Opening	○	●	○	●	—
4 Panel Central Opening	○	○	○	○	○
6 Panel Central Opening	○	○	○	○	○
Framed Glass Door (EN81-58 E60)	○	○	○	○	—
Full Glass (None E Certificate)	○	○	○	○	—
Round Glass	○	—	○	—	—
Aluminium Sill	●	●	●	●	—
Reinforced Aluminium Sill	○	○	○	○	●
Steel Sill	○	○	○	○	○
Reinforced Steel Sill	○	○	○	○	○
Door Closing	XS100	XS125	XS200	XS225	XS500
Spring	●	●	●	●	—
Spring / Counterweight	○	○	○	○	○

Controller Function	XS100	XS125	XS200	XS225	XS500
Regenerative Inverter	○	○	○	○	○
Halogen Free wiring	○	○	○	○	○
Group Control Up to 32 Lift	●	●	●	●	●
Control Box (Surface Mounted)	●	●	●	●	●
Control Box (In wall)	●	●	●	●	●
Slim Control Box (Splited parts will be in shaft)	○	○	○	○	○
Control Box in Top Landing	●	●	●	●	●
Control Box removed from shaft up to 3m	○	○	○	○	○
Control Box in any landing	○	○	○	○	○
Automatic Rescue Device to the nearest landing	●	●	●	●	●
Automatic Rescue Device to any landing	○	○	○	○	○
Generator connection	○	○	○	○	○
Service Hour Meter	○	○	○	○	○
Trip Meter	○	○	○	○	○
5 way Intercom with GSM Module	○	○	○	○	○
Advance Door Opening	○	○	○	○	○
Relevelling	○	○	○	○	○
Door nudging with audience signal	○	○	○	○	○

● Standard ○ Option – not specified

Important note

Catalogue data is indicative planning information and is not a commitment. Obtain confirmation from the engineering department before using these values in a specification or shaft design.