

BRONZE LIFT

Stride X

The premium edge of escalation - two escalator and two moving walk models for commercial and public environments.

Models

Stride X Com

Seamless mobility for sophisticated spaces. Stride X Com is a quiet, reliable escalator solution crafted for retail, office, and hospitality environments. With clean lines and understated elegance, it blends effortlessly into contemporary architecture ensuring smooth, energy-efficient movement, day after day.

Inclination 30 / 35 degrees
Step width 600 / 800 / 1000 mm
Horizontal steps 800 / 1200 mm
Speed 0.5 m/s
Rise 2-7.5 m
Up to 7300 passengers/hour
16-20 operating hours/day
Indoor / outdoor / marine

Application areas

-  Shopping mall
-  Office
-  Hotel
-  Locations and event

Stride X Transit

Durability in motion. Stride X Transit is built for high-capacity environments such as metro stations, airports, and public transit hubs. Designed for durability and safety, it offers consistent performance in demanding conditions with a clean, modern aesthetic that suits public spaces.

Inclination 30 / 35 degrees
Step width 600 / 800 / 1000 mm
Horizontal steps 800 / 1200 mm
Speed 0.5 / 0.65 m/s
Rise 2-35 m
Up to 7300 passengers/hour
20-24 operating hours/day
Indoor / outdoor / marine

Application areas

-  Public transport
-  Airport
-  Public building

Stride X Glide

Glide into efficiency. Stride X Glide offers quiet, uninterrupted horizontal mobility for modern commercial spaces. Designed to adapt across inclines and layouts, it ensures fluid transitions with minimal visual impact, all with the comfort of smooth, effortless movement.

Inclination 10 / 11 / 12 degrees
Pallet width 800 / 1000 mm
Horizontal pallets 400 mm
Speed 0.5 m/s
Rise 2-8 m
Max length 120 m
Up to 6000 passengers/hour
16-20 operating hours/day
Indoor / outdoor (covered)

Application areas

-  Shopping mall
-  Airport
-  Locations and event



Stride X Flow

Designed for distance. Stride X Flow delivers quiet, continuous horizontal transport for expansive public environments. Built for long distances and heavy foot traffic, it ensures steady, efficient movement with a clean design that integrates effortlessly into large-scale architecture.

Inclination 0 / 6 degrees

Pallet width 1000 / 1200 / 1400 mm

No horizontal pallets

Speed 0.5 m/s

Rise 0-8 m

Max length 120 m

Up to 6000 passengers/hour

20-24 operating hours/day

Indoor / outdoor (covered)

Application areas

 Airport  Public transport  Public building

Icon key

 Shopping mall  Office  Hotel  Locations and event  Public transport  Airport

 Public building

Important note

Catalogue data is indicative planning information and is not a commitment. Obtain confirmation from the engineering department before using these values in a specification or shaft design.